



# SAFETY DATA SHEET

High-Heat Resistant Paint

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : High-Heat Resistant Paint  
**Product description** : Paint  
**Product type** : Liquid.  
**UFI** : TQRA-XJX8-UNJ2-6KWC

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses                                    |        |
|--|--------|
| Consumer use<br>Industrial use<br>Professional use |        |
| Uses advised against                               | Reason |
| None identified.                                   | -      |

### 1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE  
 Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium  
 Telephone no.: +32 (0) 13 460 200  
 Fax no.: +32 (0) 13 460 201

Tor Coatings Limited  
 Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom  
 Telephone no.: +44 (0) 191 4106611  
 Fax no.: +44 (0) 191 4920125  
 enquiries@tor-coatings.com

**e-mail address of person responsible for this SDS** : rpmeurohas@rustoleum.eu

### 1.4 Emergency telephone number

National advisory body/Poison Centre

Supplier

**Telephone number** : +353 19014670  
**Hours of operation** : 24 / 7

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

## SECTION 2: Hazards identification

**Hazard pictograms**

:



**Signal word**

: Warning

**Hazard statements**

: Causes serious eye irritation.

**Precautionary statements**

**General**

: P103 - Read carefully and follow all instructions.  
P102 - Keep out of reach of children.  
P101 - If medical advice is needed, have product container or label at hand.

**Prevention**

: P280 - Wear eye or face protection.

**Response**

: Not applicable.

**Storage**

: Not applicable.

**Disposal**

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements**

: Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

**Supplemental label elements : Detergents - Regulation (EC) No 907/2006**

: Not applicable.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

: Not applicable.

**Special packaging requirements**

**Containers to be fitted with child-resistant fastenings**

: Not applicable.

**Tactile warning of danger**

: Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification**

: None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

: Mixture

**Ireland**

## SECTION 3: Composition/information on ingredients

| Product/ingredient name   | Identifiers   | %    | Regulation (EC) No. 1272/2008 [CLP]   | Type    |
|---|---|------|---|---------|
| 2-butoxyethanol   | REACH #:<br>01-2119475108-36<br>EC: 203-905-0<br>CAS: 111-76-2<br>Index: 603-014-00-0   | ≤10  | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319   | [1] [2] |
| xylene (mixture of isomeres)  | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7                         | ≤5   | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>STOT RE 2, H373<br>(oral, inhalation)<br>Asp. Tox. 1, H304  | [1] [2] |
| 2-methylpropan-1-ol   | REACH #:<br>01-2119484609-23<br>EC: 201-148-0<br>CAS: 78-83-1<br>Index: 603-108-00-1    | ≤3   | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>STOT SE 3, H336   | [1] [2] |
| methanol  | REACH #:<br>01-2119433307-44<br>EC: 200-659-6<br>CAS: 67-56-1<br>Index: 603-001-00-X    | ≤0,3 | Flam. Liq. 2, H225<br>Acute Tox. 3, H301<br>Acute Tox. 3, H311<br>Acute Tox. 3, H331<br>STOT SE 1, H370   | [1] [2] |
| pyridine-2-thiol 1-oxide, sodium salt   | EC: 223-296-5<br>CAS: 3811-73-2   | ≤0,1 | Acute Tox. 4, H302<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Aquatic Acute 1, H400<br>(M=100)   | [1]     |
| 1,2-benzisothiazol-3(2H)-one  | REACH #:<br>01-2120761540-60<br>EC: 220-120-9<br>CAS: 2634-33-5<br>Index: 613-088-00-6  | ≤0,1 | Acute Tox. 4, H302<br>Acute Tox. 2, H330<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>(M=1)   | [1]     |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | REACH #:<br>01-2120764691-48<br>EC: 611-341-5<br>CAS: 55965-84-9<br>Index: 613-167-00-5 | ≤0,1 | Aquatic Chronic 2, H411<br>Acute Tox. 3, H301<br>Acute Tox. 2, H310<br>Acute Tox. 2, H330<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1A, H317<br>Aquatic Acute 1, H400<br>(M=100)<br>Aquatic Chronic 1, H410 (M=100)<br><b>See Section 16 for the full text of the H statements declared above.</b> | [1]     |

Sweden

Type

## SECTION 3: Composition/information on ingredients

- [1] Substance classified with a health or environmental hazard  
 [2] Substance with a workplace exposure limit  
 [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII  
 [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII  
 [5] Substance of equivalent concern  
 [6] Additional disclosure due to company policy

|  |  |
|--|--|
| <p><b>SCL (Specific Concentration Limits)</b></p> <p>1,2-benzisothiazol-3(2H)-one</p> <p>reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)</p> | <p>H317 = 0.05 %</p> <p>H317 = 0.0015 %</p>        |
| <p><b>ATE (acute toxicity estimates)</b></p> <p>2-Butoxyethanol</p>  | <p>H302: ATE= 1200 mg/kg</p>                       |
| <p><b>Nanoform</b></p> <p><b>Particle characteristics</b></p> <p>This product does not contains nanomaterials.</p>   | <p><b>Particle Size</b></p> <p>Not applicable.</p> |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## SECTION 4: First aid measures

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- |              |  |
|--------------|--|
| Eye contact  | : Adverse symptoms may include the following:<br>pain or irritation<br>watering<br>redness |
| Inhalation   | : No specific data.  |
| Skin contact | : No specific data.  |
| Ingestion    | : No specific data.  |

### 4.3 Indication of any immediate medical attention and special treatment needed

- |                     |   |
|---------------------|---|
| Notes to physician  | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment.  |

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- |                                |   |
|--------------------------------|---|
| Suitable extinguishing media   | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known.   |

### 5.2 Special hazards arising from the substance or mixture

- |                                       |  |
|---------------------------------------|--|
| Hazards from the substance or mixture | : In a fire or if heated, a pressure increase will occur and the container may burst.                                    |
| Hazardous combustion products         | : Decomposition products may include the following materials:<br>carbon dioxide<br>carbon monoxide<br>metal oxide/oxides |

### 5.3 Advice for firefighters

- |  |   |
|--|---|
| Special protective actions for fire-fighters   | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.   |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |
| Additional information                         | : No unusual hazard if involved in a fire.  |

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- |                             |   |
|-----------------------------|---|
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders    | : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".   |

## SECTION 6: Accidental release measures

**6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

##### Ireland

| Product/ingredient name      | Exposure limit values   |
|------------------------------|---|
| 2-butoxyethanol              | <b>NAOSH (Ireland, 8/2018). Absorbed through skin.</b><br>OELV-15min: 246 mg/m <sup>3</sup> 15 minutes.<br>OELV-15min: 50 ppm 15 minutes.<br>OELV-8hr: 98 mg/m <sup>3</sup> 8 hours.<br>OELV-8hr: 20 ppm 8 hours.   |
| xylene (mixture of isomeres) | <b>NAOSH (Ireland, 8/2018). Absorbed through skin.</b><br>OELV-15min: 442 mg/m <sup>3</sup> 15 minutes.<br>OELV-15min: 100 ppm 15 minutes.<br>OELV-8hr: 221 mg/m <sup>3</sup> 8 hours.<br>OELV-8hr: 50 ppm 8 hours. |
| 2-methylpropan-1-ol          | <b>NAOSH (Ireland, 3/2016).</b><br>OELV-15min: 225 mg/m <sup>3</sup> 15 minutes.<br>OELV-15min: 75 ppm 15 minutes.<br>OELV-8hr: 150 mg/m <sup>3</sup> 8 hours.<br>OELV-8hr: 50 ppm 8 hours.                         |
| methanol                     | <b>NAOSH (Ireland, 8/2018). Absorbed through skin.</b><br>OELV-8hr: 260 mg/m <sup>3</sup> 8 hours.<br>OELV-8hr: 200 ppm 8 hours.  |

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

| Product/ingredient name | Type | Exposure              | Value                 | Population                     | Effects  |
|-------------------------|------|-----------------------|-----------------------|--------------------------------|----------|
| 2-butoxyethanol         | DNEL | Short term Inhalation | 426 mg/m <sup>3</sup> | Workers                        | Systemic |
|                         | DNEL | Long term Dermal      | 38 mg/kg bw/day       | Workers                        | Systemic |
|                         | DNEL | Long term Inhalation  | 49 mg/m <sup>3</sup>  | Workers                        | Systemic |
|                         | DNEL | Short term Inhalation | 135 mg/m <sup>3</sup> | General population [Consumers] | Systemic |
|                         | DNEL | Short term Inhalation | 50 mg/m <sup>3</sup>  | General population [Consumers] | Local    |
|                         | DNEL | Long term Dermal      | 75 mg/kg bw/day       | General population [Consumers] | Systemic |
|                         | DNEL | Long term Inhalation  | 20 mg/m <sup>3</sup>  | General population             | Systemic |



## SECTION 8: Exposure controls/personal protection

|                              |      |                       |                   |                                   |          |
|------------------------------|------|-----------------------|-------------------|-----------------------------------|----------|
| xylene (mixture of isomeres) | DNEL | Long term Oral        | 3,2 mg/kg bw/day  | [Consumers]<br>General population | Systemic |
|                              | DNEL | Short term Dermal     | 44,5 mg/kg bw/day | [Consumers]<br>Workers            | Systemic |
|                              | DNEL | Short term Oral       | 13,4 mg/kg bw/day | Workers                           | Systemic |
|                              | DNEL | Short term Inhalation | 123 mg/m³         | Workers                           | Local    |
|                              | DNEL | Long term Oral        | 3,2 mg/kg bw/day  | Workers                           | Systemic |
|                              | DNEL | Short term Inhalation | 442 mg/m³         | Workers                           | Local    |
|                              | DNEL | Long term Inhalation  | 221 mg/m³         | Workers                           | Local    |
|                              | DNEL | Long term Dermal      | 212 mg/kg bw/day  | Workers                           | Systemic |
|                              | DNEL | Long term Inhalation  | 65,3 mg/m³        | General population                | Systemic |
|                              | DNEL | Long term Dermal      | 125 mg/kg bw/day  | General population                | Systemic |
| 2-methylpropan-1-ol          | DNEL | Long term Oral        | 125 mg/kg bw/day  | General population                | Systemic |
|                              | DNEL | Long term Inhalation  | 310 mg/m³         | Workers                           | Local    |
|                              | DNEL | Long term Oral        | 25 mg/kg bw/day   | General population                | Systemic |
|                              | DNEL | Long term Inhalation  | 55 mg/m³          | [Consumers]<br>General population | Local    |

### PNECs

| Product/ingredient name      | Compartment Detail     | Value        | Method Detail            |
|------------------------------|------------------------|--------------|--------------------------|
| 2-butoxyethanol              | Fresh water            | 8,8 mg/l     | -                        |
|                              | Marine                 | 0,88 mg/l    | -                        |
|                              | Sewage Treatment Plant | 463 mg/l     | -                        |
|                              | Fresh water sediment   | 34,6 mg/kg   | -                        |
|                              | Marine water sediment  | 3,46 mg/kg   | -                        |
| xylene (mixture of isomeres) | Secondary Poisoning    | 2,8 mg/kg    | -                        |
|                              | Fresh water            | 0,327 mg/l   | Sensitivity Distribution |
|                              | Marine water           | 0,327 mg/l   | Sensitivity Distribution |
|                              | Fresh water sediment   | 12,46 mg/kg  | Equilibrium Partitioning |
|                              | Marine water sediment  | 12,46 mg/kg  | Equilibrium Partitioning |
| 2-methylpropan-1-ol          | Soil                   | 2,31 mg/kg   | Equilibrium Partitioning |
|                              | Sewage Treatment Plant | 6,58 mg/l    | -                        |
|                              | Fresh water            | 0,4 mg/l     | -                        |
|                              | Marine water           | 0,04 mg/l    | -                        |
|                              | Sewage Treatment Plant | 10 mg/l      | -                        |
|                              | Fresh water sediment   | 1,52 mg/kg   | -                        |
|                              | Marine water sediment  | 0,125 mg/kg  | -                        |
|                              | Soil                   | 0,0699 mg/kg | -                        |

### 8.2 Exposure controls

#### Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.



## SECTION 8: Exposure controls/personal protection

### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. (EN 166)

### Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): > 8 hours (breakthrough time): nitrile rubber (0.5mm)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

- Respiratory protection** : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: During fumigation/spraying wear suitable respiratory equipment. organic vapour (Type A) and particulate filter (EN 140)

- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

|  |   |
|--|---|
| Physical state                               | : Liquid.   |
| Colour                                       | : Black.  |
| Odour  | : Not available.                                      |
| Odour threshold                              | : Not available.                                      |
| Melting point/freezing point                 | : Not available.                                      |
| Initial boiling point and boiling range      | : Not relevant due to nature of the product.          |
| Flammability (solid, gas)                    | : Not available.                                      |
| Upper/lower flammability or explosive limits | : Not available.                                      |
| Flash point                                  | : Closed cup: >60°C (>140°F) [ASTM D 56]              |
| Auto-ignition temperature                    | : Not relevant due to nature of the product.          |
| Decomposition temperature                    | : Not available.                                      |
| pH   | : 7 to 9 [OECD 122]                                   |
| pH : Justification                           | : Not available.                                      |
| Viscosity                                    | : Dynamic: 80 to 120 mPa·s                            |
| Solubility(ies)                              | : Not available.                                      |
| Solubility in water                          | : Not available.                                      |
| Partition coefficient: n-octanol/ water      | : Not applicable.                                     |
| Vapour pressure                              | : Not relevant due to nature of the product.          |
| Evaporation rate                             | : Not available.                                      |
| Relative density                             | : 1 to 1,1 [calculated.]                              |
| Density                                      | : 1,097 g/cm <sup>3</sup> [20°C (68°F)] [calculated.] |
| Vapour density                               | : Not available.                                      |
| Explosive properties                         | : Not available.                                      |
| Oxidising properties                         | : Not available.                                      |
| <u>Particle characteristics</u>              |   |
| Median particle size                         | : Not applicable.                                     |

## SECTION 10: Stability and reactivity

|   |  |
|---|--|
| 10.1 Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability                 | : The product is stable.   |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.            |
| 10.4 Conditions to avoid                | : No specific data.  |
| 10.5 Incompatible materials             | : No specific data.  |

## SECTION 10: Stability and reactivity

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO<sub>2</sub> and smoke can be generated.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

| Product/ingredient name   | Result                          | Species            | Dose                    | Exposure |
|---|---------------------------------|--------------------|-------------------------|----------|
| 2-butoxyethanol   | LC50 Inhalation Vapour          | Rat                | 10 to 20 mg/l           | 4 hours  |
|   | LD50 Dermal                     | Rabbit             | 667 to 1060 mg/kg       | -        |
|   | LD50 Oral                       | Guinea pig         | 1414 mg/kg              | -        |
|   | LD50 Oral                       | Guinea pig         | 1400 mg/kg              | -        |
|   | LD50 Oral                       | Rat                | 1300 mg/kg              | -        |
|   | LD50 Oral                       | Rat                | 1746 mg/kg              | -        |
| xylene (mixture of isomeres)  | LD50 Oral                       | Rat                | 1400 mg/kg              | -        |
|   | LC50 Inhalation Gas.            | Rat                | 5000 ppm                | 4 hours  |
|   | LC50 Inhalation Gas.            | Rat                | 6670 ppm                | 4 hours  |
|   | LC50 Inhalation Vapour          | Rat                | 29091 mg/m <sup>3</sup> | 4 hours  |
|   | LD50 Dermal                     | Rabbit             | 4,2 g/kg                | -        |
|   | LD50 Oral                       | Rat                | 4300 mg/kg              | -        |
| 2-methylpropan-1-ol   | TDLo Dermal                     | Rabbit             | 4300 mg/kg              | -        |
|   | LC50 Inhalation Vapour          | Rat                | 19200 mg/m <sup>3</sup> | 4 hours  |
|   | LC50 Inhalation Vapour          | Rat                | >8000 ppm               | 4 hours  |
|   | LD50 Dermal                     | Rabbit             | 3400 mg/kg              | -        |
|   | LD50 Oral                       | Mouse              | 3500 mg/kg              | -        |
|   | LD50 Oral                       | Rat                | 2460 mg/kg              | -        |
| methanol  | LC50 Inhalation Gas.            | Cat                | 23600 ppm               | 6 hours  |
|   | LC50 Inhalation Gas.            | Rat                | 145000 ppm              | 1 hours  |
|   | LD50 Intraperitoneal            | Rabbit             | 1826 mg/kg              | -        |
|   | LD50 Oral                       | Mouse              | 5800 mg/kg              | -        |
| 1,2-benzisothiazol-3(2H)-one  | LC50 Inhalation Dusts and mists | Rat                | 0,11 mg/l               | 4 hours  |
|   | LC50 Inhalation Dusts and mists | Rat - Male, Female | 0,5 mg/l                | 4 hours  |
|   | LD50 Oral                       | Rat - Male         | 490 mg/kg               | -        |
|   | LC50 Inhalation Dusts and mists | Rat - Male, Female | 0,171 mg/l              | 4 hours  |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | LC50 Inhalation Dusts and mists | Rat - Male, Female | 0,171 mg/l              | 4 hours  |
|   | LD50 Dermal                     | Rabbit             | 92,4 mg/kg              | -        |
|   | LD50 Oral                       | Rat                | 64 mg/kg                | -        |

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Acute toxicity estimates

| Product/ingredient name  | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| 2-butoxyethanol  | 1300         | 1100           | N/A                      | N/A                         | 1,5                                 |
| xylene (mixture of isomeres)   | 4300         | 1100           | N/A                      | 11                          | N/A                                 |
| 2-methylpropan-1-ol  | 2460         | 3400           | N/A                      | N/A                         | N/A                                 |
| methanol   | 100          | 300            | 72500                    | 3                           | N/A                                 |
| pyridine-2-thiol 1-oxide, sodium salt  | 500          | 1100           | N/A                      | N/A                         | 1,5                                 |
| 1,2-benzisothiazol-3(2H)-one   | 490          | N/A            | N/A                      | 0,5                         | N/A                                 |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- | 64           | 92,4           | N/A                      | N/A                         | 0,171                               |

## SECTION 11: Toxicological information

isothiazol-3-one [EC no. 220-239-6] (3:1)

### Irritation/Corrosion

| Product/ingredient name   | Result                   | Species | Score | Exposure                | Observation  |
|---|--------------------------|---------|-------|-------------------------|--------------|
| 2-butoxyethanol   | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 100 milligrams | -            |
|   | Eyes - Severe irritant   | Rabbit  | -     | 100 milligrams          | -            |
|   | Skin - Mild irritant     | Rabbit  | -     | 500 milligrams          | -            |
| xylene (mixture of isomeres)  | Eyes - Mild irritant     | Rabbit  | -     | 87 milligrams           | -            |
|   | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 5 milligrams   | -            |
|   | Skin - Mild irritant     | Rat     | -     | 8 hours 60 microliters  | -            |
|   | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 milligrams | -            |
|   | Skin - Moderate irritant | Rabbit  | -     | 100 Percent             | -            |
| 2-methylpropan-1-ol   | Eyes - Moderate irritant | Rabbit  | -     | -                       | -            |
|   | Skin - Irritant          | Rabbit  | -     | -                       | -            |
|   | Eyes - Irritant          | Rabbit  | -     | -                       | -            |
| methanol  | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 100 milligrams | -            |
|   | Eyes - Moderate irritant | Rabbit  | -     | 40 milligrams           | -            |
|   | Skin - Moderate irritant | Rabbit  | -     | 24 hours 20 milligrams  | -            |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | Skin - Severe irritant   | Human   | -     | 0.01 Percent            | -            |
|   | Skin - Severe irritant   | Rabbit  | -     | -                       | 1 to 4 hours |
|   | Eyes - Severe irritant   | Rabbit  | -     | -                       | -            |

### Conclusion/Summary

- Skin** : Based on available data, the classification criteria are not met.
- Eyes** : Causes serious eye irritation.
- Respiratory** : Based on available data, the classification criteria are not met.

### Sensitisation

| Product/ingredient name  | Route of exposure | Species                  | Result                     |
|--|-------------------|--------------------------|----------------------------|
| 1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | skin<br>skin      | Guinea pig<br>Guinea pig | Sensitising<br>Sensitising |

### Conclusion/Summary

- Skin** : Based on available data, the classification criteria are not met.
- Respiratory** : Based on available data, the classification criteria are not met.

### Mutagenicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

## SECTION 11: Toxicological information

### Reproductive toxicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

| Product/ingredient name      | Category                 | Route of exposure | Target organs                |
|------------------------------|--------------------------|-------------------|------------------------------|
| xylene (mixture of isomeres) | Category 3               | -                 | Respiratory tract irritation |
| 2-methylpropan-1-ol          | Category 3               | -                 | Respiratory tract irritation |
| methanol                     | Category 3<br>Category 1 | -                 | Narcotic effects<br>-        |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name      | Category   | Route of exposure | Target organs |
|------------------------------|------------|-------------------|---------------|
| xylene (mixture of isomeres) | Category 2 | oral, inhalation  | -             |

### Aspiration hazard

| Product/ingredient name      | Result                         |
|------------------------------|--------------------------------|
| xylene (mixture of isomeres) | ASPIRATION HAZARD - Category 1 |

**Information on likely routes of exposure** : Routes of entry anticipated: Dermal, Inhalation.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness  
**Inhalation** : No specific data.  
**Skin contact** : No specific data.  
**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

### Potential chronic health effects

## SECTION 11: Toxicological information

Not available.

|                              |   |
|------------------------------|---|
| <b>Conclusion/Summary</b>    | : Based on available data, the classification criteria are not met. |
| <b>General</b>               | : No known significant effects or critical hazards.                 |
| <b>Carcinogenicity</b>       | : No known significant effects or critical hazards.                 |
| <b>Mutagenicity</b>          | : No known significant effects or critical hazards.                 |
| <b>Reproductive toxicity</b> | : No known significant effects or critical hazards.                 |

**Endocrine disrupting properties** : Not available.

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name                  | Result   | Species  | Exposure  |
|--|--|--|---|
| 2-butoxyethanol                          | Acute EC50 1700 to 1940 mg/l<br>Acute EC50 >1000 mg/l Fresh water<br>Acute LC50 1000 mg/l Marine water   | Daphnia spec. - Daphnia magna<br>Daphnia spec. - Daphnia magna<br>Crustaceans -<br>Chaetogammarus marinus -<br>Young   | 24 hours<br>48 hours<br>48 hours  |
| xylene (mixture of isomeres)             | Acute LC50 1000 to 800000 µg/l<br>Marine water<br>Acute LC50 1490000 µg/l Fresh water<br>Acute LC50 1250000 µg/l Marine water  | Crustaceans - Crangon crangon<br>Fish - Lepomis macrochirus<br>Fish - Menidia beryllina  | 48 hours<br>96 hours<br>96 hours  |
| 2-methylpropan-1-ol                      | Acute EC50 1,3 mg/l Fresh water<br>Acute LC50 1 mg/l Fresh water<br>Acute NOEC 0,44 mg/l<br>Chronic NOEC 0,96 mg/l Fresh water<br>Acute EC50 1300 to 1200000 µg/l<br>Fresh water<br>Acute EC50 1933 to 1439000 µg/l<br>Fresh water<br>Acute LC50 600000 µg/l Marine water                  | Algae<br>Daphnia spec.<br>Algae<br>Daphnia spec.<br>Crustaceans - Ceriodaphnia<br>reticulata - Larvae<br>Daphnia spec. - Daphnia magna<br>Crustaceans - Artemia salina -<br>Nauplii  | 72 hours<br>24 hours<br>72 hours<br>21 days<br>48 hours<br>48 hours             |
| methanol                                 | Acute LC50 1030000 µg/l Fresh water<br>Acute LC50 1600000 µg/l Fresh water<br>Acute LC50 1670 to 1510000 µg/l<br>Fresh water<br>Acute LC50 1520 to 1330000 µg/l<br>Fresh water<br>Chronic NOEC mg/l Fresh water<br>Acute EC50 16,912 mg/l Marine water<br>Acute LC50 3289 mg/l Fresh water | Daphnia spec. - Daphnia magna<br>Fish - Lepomis macrochirus<br>Fish - Pimephales promelas<br>Fish - Oncorhynchus mykiss<br>Daphnia spec. - Daphnia magna<br>Algae - Ulva pertusa<br>Daphnia spec. - Daphnia<br>magna - Neonate | 48 hours<br>96 hours<br>96 hours<br>96 hours<br>21 days<br>96 hours<br>48 hours |
| pyridine-2-thiol 1-oxide,<br>sodium salt | Acute LC50 1000 mg/l Fresh water<br>Acute LC50 100 mg/l Fresh water  | Fish - Lepomis macrochirus<br>Fish - Pimephales promelas -<br>Juvenile (Fledgling, Hatchling,<br>Weanling)   | 96 hours<br>96 hours  |
| 1,2-benzisothiazol-3(2H)-one             | Acute LC50 290 mg/l Fresh water<br>Acute EC50 0,022 mg/l<br>Acute LC50 10 mg/l<br>Acute EC50 0,067 mg/l<br>Acute EC50 0,11 mg/l<br>Acute EC50 0,9893 mg/l Marine water   | Fish - Danio rerio - Egg<br>Daphnia spec.<br>Fish<br>Algae - Pseudokirchneriella<br>subcapitata<br>Algae<br>Crustaceans - Opossum Shrimp   | 96 hours<br>48 hours<br>24 hours<br>72 hours<br>72 hours<br>96 hours            |

## SECTION 12: Ecological information

|   |  |  |   |
|---|--|--|---|
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | Acute EC50 2,94 mg/l Fresh water<br>Acute LC50 8 to 13 mg/l<br>Acute LC50 2,18 mg/l Fresh water<br>Acute LC50 1,6 to 2,8 ppm Fresh water<br>Chronic NOEC 90 mg/l           | Daphnia spec.<br>Fish - Alburnus alburnus<br>Fish<br>Fish - Oncorhynchus mykiss<br>Aquatic plants - Phaseolus vulgaris | 48 hours<br>96 hours<br>96 hours<br>96 hours<br>20 days |
|   | Chronic NOEC 1,2 mg/l<br>Chronic NOEC 0,21 mg/l<br>Chronic NOEL 0,0403 mg/l<br>Acute EC50 0,037 mg/l Fresh water   | Daphnia spec.<br>Fish<br>Algae<br>Algae  | 21 days<br>28 days<br>72 hours<br>48 hours              |
|   | Acute EC50 0,16 mg/l Fresh water<br>Acute LC50 0,19 mg/l Fresh water<br>Acute NOEC 0,004 mg/l Marine water<br>Chronic NOEC 0,18 mg/l<br>Chronic NOEC 0,02 mg/l Fresh water | Daphnia spec.<br>Fish<br>Algae<br>Daphnia spec.<br>Fish  | 48 hours<br>96 hours<br>48 hours<br>21 days<br>38 days  |

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

| Product/ingredient name   | Test                   | Result  | Dose   | Inoculum |
|---|------------------------|---|--------|----------|
| 2-butoxyethanol   | OECD 301B<br>OECD 301E | 90,4 % - Readily - 28 days<br>>70 % - Readily - 28 days | -<br>- | -<br>-   |
| xylene (mixture of isomeres)  | -                      | 32,27 % - Inherent - 5 days                             | -      | -        |
| 2-methylpropan-1-ol   | OECD 301F              | 90 % - Readily - 5 days<br>87,8 % - 28 days             | -<br>- | -<br>-   |
| 1,2-benzisothiazol-3(2H)-one  | -                      | 70 to 80 % - 28 days                                    | -      | -        |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | OECD 303A<br>OECD 301D | >90 % - Readily - 1 days<br>>60 % - Readily - 28 days   | -<br>- | -<br>-   |
|   | -                      | <50 % - 10 days   | -      | -        |

**Conclusion/Summary** : This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.

| Product/ingredient name   | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| 2-butoxyethanol   | -                 | -          | Readily          |
| xylene (mixture of isomeres)  | -                 | -          | Readily          |
| 2-methylpropan-1-ol   | -                 | -          | Readily          |
| methanol  | -                 | -          | Readily          |
| 1,2-benzisothiazol-3(2H)-one  | -                 | -          | Readily          |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | -                 | -          | Readily          |

### 12.3 Bioaccumulative potential



## SECTION 12: Ecological information

| Product/ingredient name   | LogP <sub>ow</sub> | BCF         | Potential |
|---|--------------------|-------------|-----------|
| 2-butoxyethanol   | 0,81               | 3,2         | low       |
| xylene (mixture of isomeres)  | 3,12               | 8.1 to 25.9 | low       |
| 2-methylpropan-1-ol   | 1                  | -           | low       |
| methanol  | -0,77              | <10         | low       |
| 1,2-benzisothiazol-3(2H)-one  | 0,64               | -           | low       |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | -0.83 to 0.75      | -           | low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Nonvolatile liquid.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Endocrine disrupting properties** : No known significant effects or critical hazards.

**12.7 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

#### European waste catalogue (EWC)

| Waste code | Waste designation  |
|------------|--|
| 08 01 12   | waste paint and varnish other than those mentioned in 08 01 11 |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|                                 | ADR/RID        | ADN            | IMDG           | IATA           |
|---------------------------------|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number     | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name    | -              | -              | -              | -              |
| 14.3 Transport hazard class(es) | -              | -              | -              | -              |
| 14.4 Packing group              | -              | -              | -              | -              |
| 14.5 Environmental hazards      | No.            | No.            | No.            | No.            |
|                                 |                |                |                |                |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** : IIA/i. One-pack performance coatings. EU limit value for this product : 140g/l (2010.) This product contains a maximum of 70 g/l VOC.

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

High-Heat Resistant Paint

## SECTION 15: Regulatory information

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

### Ozone depleting substances (1005/2009/EC)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EC)

Not listed.

### Persistent Organic Pollutants (850/2004/EC)

Not listed.

### Seveso Directive

This product is not controlled under the Seveso Directive.

### Ireland

**References** : Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001 (S.I. No. 619 of 2001)  
Safety, Health and Welfare at Work (Carcinogens) Regulations 2001 (S.I. No. 78 of 2001)  
Safety, Health and Welfare at Work (General Application) Regulations 2007  
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878  
REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

### International regulations

#### Stockholm Convention on Persistent Organic Pollutants

| List name   | Ingredient name | Status |
|-------------|-----------------|--------|
| Not listed. |                 |        |

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

| List name   | Ingredient name | Status |
|-------------|-----------------|--------|
| Not listed. |                 |        |

**CN code** : 3209 10 00

### Inventory list

**Australia** : At least one component is not listed.  
**Canada** : At least one component is not listed.  
**China** : Not determined.  
**Europe** : All components are listed or exempted.  
**Japan** : **Japan inventory (CSCL)**: Not determined.  
**Japan inventory (ISHL)**: Not determined.  
**New Zealand** : At least one component is not listed.  
**Philippines** : At least one component is not listed.  
**Republic of Korea** : At least one component is not listed.  
**Taiwan** : At least one component is not listed.  
**Thailand** : Not determined.  
**Turkey** : Not determined.  
**United States** : Not determined.

High-Heat Resistant Paint

## SECTION 15: Regulatory information

**Viet Nam** : Not determined.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification     | Justification   |
|--------------------|-----------------|
| Eye Irrit. 2, H319 | Expert judgment |

### Full text of abbreviated H statements

#### Ireland

|  |  |
|--|--|
| <b>Full text of abbreviated H statements</b> : | <div> <div>H225</div> <div>Highly flammable liquid and vapour.</div> </div> <div> <div>H226</div> <div>Flammable liquid and vapour.</div> </div> <div> <div>H301</div> <div>Toxic if swallowed.</div> </div> <div> <div>H302</div> <div>Harmful if swallowed.</div> </div> <div> <div>H304</div> <div>May be fatal if swallowed and enters airways.</div> </div> <div> <div>H310</div> <div>Fatal in contact with skin.</div> </div> <div> <div>H311</div> <div>Toxic in contact with skin.</div> </div> <div> <div>H312</div> <div>Harmful in contact with skin.</div> </div> <div> <div>H314</div> <div>Causes severe skin burns and eye damage.</div> </div> <div> <div>H315</div> <div>Causes skin irritation.</div> </div> <div> <div>H317</div> <div>May cause an allergic skin reaction.</div> </div> <div> <div>H318</div> <div>Causes serious eye damage.</div> </div> <div> <div>H319</div> <div>Causes serious eye irritation.</div> </div> <div> <div>H330</div> <div>Fatal if inhaled.</div> </div> <div> <div>H331</div> <div>Toxic if inhaled.</div> </div> <div> <div>H332</div> <div>Harmful if inhaled.</div> </div> <div> <div>H335</div> <div>May cause respiratory irritation.</div> </div> <div> <div>H336</div> <div>May cause drowsiness or dizziness.</div> </div> <div> <div>H370</div> <div>Causes damage to organs.</div> </div> <div> <div>H373</div> <div>May cause damage to organs through prolonged or repeated exposure.</div> </div> <div> <div>H400</div> <div>Very toxic to aquatic life.</div> </div> <div> <div>H410</div> <div>Very toxic to aquatic life with long lasting effects.</div> </div> <div> <div>H411</div> <div>Toxic to aquatic life with long lasting effects.</div> </div> |
|--|--|

## SECTION 16: Other information

[Full text of classifications \[CLP/GHS\]](#)

|                   |   |
|-------------------|---|
| Acute Tox. 2      | ACUTE TOXICITY - Category 2                                     |
| Acute Tox. 3      | ACUTE TOXICITY - Category 3                                     |
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Acute 1   | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1                  |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1                 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2                 |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                  |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                  |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                  |
| Flam. Liq. 2      | FLAMMABLE LIQUIDS - Category 2                                  |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                  |
| Skin Corr. 1B     | SKIN CORROSION/IRRITATION - Category 1B                         |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                          |
| Skin Sens. 1      | SKIN SENSITISATION - Category 1                                 |
| Skin Sens. 1A     | SKIN SENSITISATION - Category 1A                                |
| STOT RE 2         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |
| STOT SE 1         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1   |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3   |

Date of printing : 10/06/2021

Date of issue/ Date of revision : 10/06/2021

Date of previous issue : 10/06/2021

Version : 3

[Notice to reader](#)

**IMPORTANT NOTE:** The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

**MANUFACTURER'S DISCLAIMER:** the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.