



DEKS OLJE D2®

EXOTIC WOOD FINISH

USAGE

- For use on woods pre-treated with Deks Olje D1® (or Owatrol oil® or Xylkote Interior oil®).
- Exterior: garden furniture, fences, stairs, boats...etc.
- Interior: doors, windows, stairs, bathrooms, frames...etc.
- Horizontal and Vertical surfaces.
- Hardwoods and Exotic Tropical woods such as Teak, Ipé, Bovinga, Bolondo and Iroco.
- On boats, Deks Olje D2® can be used for all applications above the water line.

HIGH GLOSS FINISH FOR INTERIOR AND EXTERIOR

- Light and resistant film that avoids peeling, scaling, cracking or blistering.
- High gloss, very durable finish.
- Flexible finish (like varnish) which does not hide the wood's veins.
- Easy maintenance, simply wash regularly with water.
- Fast refurbishing, no sanding between coats.



RECOMENDATIONS PRIOR TO APPLICATION

- Wood should be treated with Deks Olje D1® prior to Deks Olje D2®. In some cases Owatrol Oil® or Xylkote interior oil may be used.
- The wood surface should be clean and dry.
- Do not dilute.



APPLICATION

- Apply 3 to 6 coats of Deks Olje D2® depending on exposure of surface.
- Allow at least 12 hours drying between coats.
- There is no need for sanding between coats.
- Allow 3 to 4 days drying before putting surface in use.

Note: Clean any dripping or drops of Deks Olje D2® from surface before the product dries. Once dry, spots will form and they will be very hard to eliminate.

COVERAGE	APPLICATION TOOLS	TEMPERATURE FOR APPLICATION	DRYING TIME	CLEAN UP	OWATROL INTERNATIONAL
15 m ² /l		+10°C +8°C	24 hours initial drying before use 3 days		