

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : EVO RAL COLOUR
UFI : QT10-H0S7-R00U-QNM5
Product code : EVO
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Use of the substance/mixture : Spraying paint (spray can)

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Novasol Spray, S.A.
P.I.: Empalme - C/ Empalme, 27
43712 Llorenç del Penedès - Spain
T +34 977 677 305 - F +34 977 678 072
novasol@novasolspray.com - www.novasolspray.com

1.4. Emergency telephone number

Emergency number : +34 977 677 305
Office hours: Monday-Friday 8:30 AM-6:00 PM GMT+1

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Contains :

n-butyl acetate; ethyl acetate; butanone; ethyl methyl ketone; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	<p>H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.</p> <p>: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P271 - Use only outdoors or in a well-ventilated area. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.</p>
EUH-statements	<p>: EUH066 - Repeated exposure may cause skin dryness or cracking. EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.</p>
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butanone; ethyl methyl ketone substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3 REACH-no: 01-2119457290-43	≥ 5 – < 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	< 15	Flam. Liq. 3, H226 STOT SE 3, H336
ethyl acetate substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	< 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC-No.: 919-857-5 REACH-no: 01-2119463258-33	< 15	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
Xylene substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	≥ 1 – < 10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-002 REACH-no: 01-2119489379-17	≥ 1 – < 10	Carc. 2, H351

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethylbenzene substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	< 3	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	< 1	Flam. Liq. 3, H226

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m ³
IOEL STEL	723 mg/m ³
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethyl acetate (141-78-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethyl acetate
IOEL TWA	734 mg/m ³
IOEL STEL	1468 mg/m ³
IOEL STEL [ppm]	400 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
2-methoxy-1-methylethyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m ³
IOEL STEL	550 mg/m ³
IOEL STEL [ppm]	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
butanone; ethyl methyl ketone (78-93-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Butanone
IOEL TWA	600 mg/m ³
IOEL STEL	900 mg/m ³
IOEL STEL [ppm]	300 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m ³
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
ethylbenzene (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylbenzene
IOEL TWA	442 mg/m ³
IOEL STEL	884 mg/m ³
IOEL STEL [ppm]	200 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

eye protection (EN166)

8.2.2.2. Skin protection

Hand protection:

Butyl rubber gloves (EN 374)

8.2.2.3. Respiratory protection

Respiratory protection:

If vapour is released : Disposable half mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Various.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: < 0 °C Aerosol jet
Flash point	: < -60 °C Aerosol jet
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

Not volatile	: 18 wt%
VOC content	: 82 wt%
VOC content	: 620 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

n-butyl acetate (123-86-4)

LD50 oral	10760
LD50 dermal	> 14112
LC50 Inhalation - Rat	23,4

ethyl acetate (141-78-6)

LD50 oral rat	4100 mg/kg
LD50 dermal rabbit	20000 mg/kg
LC50 Inhalation - Rat	> 44 g/m ³
LC50 Inhalation - Rat (Vapours)	22,5 mg/l/4h

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-methoxy-1-methylethyl acetate (108-65-6)	
LD50 oral rat	8532 mg/kg
LD50 dermal rat	5100
LC50 Inhalation - Rat	> 10,8
LC50 Inhalation - Rat (Vapours)	30 mg/l/4h
butanone; ethyl methyl ketone (78-93-3)	
LD50 oral rat	4000 mg/kg
LD50 dermal rabbit	6400 mg/kg
LC50 Inhalation - Rat	23,5 mg/l/4h
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LD50 oral	> 10000 mg/kg
LD50 dermal	> 10000 mg/kg
LC50 Inhalation - Rat	> 6,8 mg/l/4h
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
LD50 oral rat	5100 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal	> 5000
LC50 Inhalation - Rat	4951
Xylene (1330-20-7)	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
ethylbenzene (100-41-4)	
LD50 oral	3500
LC50 Inhalation - Rat	17,2
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
Xylene (1330-20-7)	
IARC group	3 - Not classifiable
ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
butanone; ethyl methyl ketone (78-93-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
EVO RAL COLOUR	
Vaporizer	Aerosol

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 96h fish (1)	161 mg/l
EC50 - Crustacea [1]	481 mg/l
butanone; ethyl methyl ketone (78-93-3)	
LC50 96h fish (1)	3220 mg/l
EC50 - Crustacea [1]	5091 mg/l
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
LC50 96h fish (1)	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19,3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27,8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 2,92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Xylene (1330-20-7)

LC50 96h fish (1)	2,6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3,4 mg/l Test organisms (species): Ceriodaphnia dubia
NOEC chronic fish	> 1,3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

ethylbenzene (100-41-4)

LC50 96h fish (1)	5,1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	4,9 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	5,4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	7,7 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	3,6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	1,7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0,96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

2-methoxy-1-methylethyl acetate (108-65-6)

BCF - Fish [1]	1
Partition coefficient n-octanol/water (Log Pow)	0,43

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information




In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number		
UN 1950	UN 1950	UN 1950

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA
14.2. UN proper shipping name		
AEROSOLS	AEROSOLS	Aerosols, flammable
Transport document description		
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A145, A167, A802
ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3(a)	EVO RAL COLOUR ; n-butyl acetate ; ethyl acetate ; 2-methoxy-1-methylethyl acetate ; butanone; ethyl methyl ketone ; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; Xylene ; ethylbenzene
3(b)	EVO RAL COLOUR ; n-butyl acetate ; ethyl acetate ; butanone; ethyl methyl ketone ; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; Xylene ; ethylbenzene
3(c)	ethylbenzene
40.	n-butyl acetate ; ethyl acetate ; 2-methoxy-1-methylethyl acetate ; butanone; ethyl methyl ketone ; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; Xylene ; ethylbenzene

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 82 wt%

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830.

Indication of changes

Section	Changed item	Change	Comments
	Classification code (RID)	Added	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
2.1	Adverse physicochemical, human health and environmental effects	Modified	
2.2	Precautionary statements (CLP)	Modified	
2.2	Hazard statements (CLP)	Modified	
4.1	First-aid measures after skin contact	Modified	
4.2	Symptoms/effects after skin contact	Modified	

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Indication of changes			
Section	Changed item	Change	Comments
6.1	Emergency procedures	Modified	
7.1	Hygiene measures	Modified	
7.1	Precautions for safe handling	Modified	

Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified

EVO RAL COLOUR

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Abbreviations and acronyms

vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Aerosol 1	H222;H229	Expert judgment
Eye Irrit. 2	H319	Expert judgment
STOT SE 3	H336	Expert judgment

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.