



ANTI-RUST GRAPHENE PRIMER

Nitromors Anti-Rust Graphene Primer offers brilliant coverage and protection, exceptional adhesion to metals, and is suitable for both water-based and oil based topcoats. This unique formula is fast drying, provides a smooth matt finish and is incredibly resistance to rust and corrosion. Nitromors Anti-Rust Graphene Primer has excellent compatibility with most automotive finishes including rigid plastics and is ideal for use after Nitromors Rust Remover.




HOW TO USE

1. Ensure area to be primed is free from dust, flakes of rust, grime, greases, and oils etc. by abrading the surface where required and wipe with a cloth dampened with white spirit.
2. Allow to dry.
3. Shake the can for at least 2 minutes, repeat shaking at regular intervals during use.
4. Apply sparingly from a distance of 15-25cm. Apply 2 to 3 light coats as necessary to achieve total and even coverage, leaving 15 minutes between each application.
5. Allow to dry for 24 hours to develop the maximum primer hardness.
6. After use, invert can and spray for a few seconds to clear nozzle.

■ Appearance	Coloured liquids with characteristic paint odours.
■ Specific Gravity	0.950 +/- 0.015
■ Viscosity	Medium Viscosity liquids.
■ Active Content % m/m	10 to 25
■ Flammability	Extremely flammable aerosol.
■ Composition Data	Dispersion of resins, pigment, fillers, corrosion inhibitors, plasticizers and thixotropic agents in a predominantly aromatic solvent system with liquified propellants.

Product Code	Size	Barcode
NRP500	500ml	5010373142929



ENVIRONMENTAL PROTECTION & SAFETY PRECAUTIONS



Danger - Extremely flammable aerosol. Pressurised container: may burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapour/spray. Use only outdoors or in a well ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice /attention. Protect from sunlight. Do not expose to temperatures exceeding 50 C/122 F. Dispose of contents/container in accordance with local regulations. Repeated exposure may cause skin dryness or cracking. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains: Acetone, Butanone, n-butyl acetate. Use only as a directed.