

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : OWATROL OIL Product code : RO001.

**1.2. Relevant identified uses of the substance or mixture and uses advised against** Penetrating anti-rust primer - Paint Additive

### 1.3. Details of the supplier of the safety data sheet

Registered company name : DURIEU S.A..

Address : Z.I. "La Marinière" 2 bis, rue Charles de Gaulle.91070.BONDOUFLE.FRANCE.

Telephone : + 33 (0)1.60.86.48.70. Fax : + 33 (0)1.60.86.84.84.

info@durieu.com

## www.durieu.com

## 1.4. Emergency telephone number : + 33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

### Other emergency numbers

UNITED KINGDOM :UK National poisons emergency number: +44 (0) 870 600 6266 IRELAND, EIRE: Ireland National Poisons Information Centre: +353 (0) 1 8379964 AUSTRALIA: Poison Information Centre: 131 126 NEW ZEALAND: Poison Information Centre 0 800 764 766:

### **SECTION 2 : HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

### In compliance with EC regulation No. 1272/2008 and its amendments.

Repeated exposure may cause skin dryness or cracking (EUH066).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

#### 2.2. Label elements

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard statements :	
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements - 0	Seneral :
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Precautionary statements - F	Prevention :
P260	Do not breathe dust vapours.
P262	Do not get in eyes, on skin, or on clothing.
P273	Avoid release to the environment.
Precautionary statements - F	Response :
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
Precautionary statements - I	Disposal :
P501	Dispose of contents / container in a waste collection point.

### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

### SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

### **Composition :**

## SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) RUSTOL-OWATROL / OWATROL OIL - RO001

dentification	(EC) 1272/2008	Note	%
NDEX: PCP186	GHS08		25 <= x % < 50
EC: 918-481-9	Dgr		
REACH: 01-2119457273-39	Asp. Tox. 1, H304		
	EUH:066		
HYDROCARBONS, C10-C13,			
N-ALKANES, ISOALKANES, CYCLICS,			
<2% AROMATICS			
NDEX: 298	GHS09, GHS07, GHS08		2.5 <= x % < 10
EC: 918-811-1	Dgr		
REACH: 01-2119463583-34	Asp. Tox. 1, H304		
	STOT SE 3, H336		
HYDROCARBONS, C10, AROMATICS,	Aquatic Chronic 2, H411		
<1% NAPHTALENE	EUH:066		

(Full text of H-phrases: see section 16)

#### Other data :

According to Note 4 of Directive 2001/59/CE the preparation is not considered as non viscous (fluid).

### **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

## 4.1. Description of first aid measures

### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

#### In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

### In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor. Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

#### **SECTION 5 : FIREFIGHTING MEASURES**

#### This product is not classed as flammable.

### 5.1. Extinguishing media

In case of fire, use specifically adapted extinguishing media.

## Suitable methods of extinction

- In the event of a fire, use :
- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)
- water with AFFF (Aqueous Film Forming Foam) additive
- halon

## Unsuitable methods of extinction

Direct water jet.

## 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

- Do not breathe in smoke.
- In the event of a fire, the following may be formed :
- carbon monoxide (CO)

### - carbon dioxide (CO2)

#### 5.3. Advice for firefighters

No data available.

#### **SECTION 6 : ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

### For non first aid worker

Avoid any contact with the skin and eyes.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

Although this product is not flammable, rags soaked in it, may spontaneously ignite if improperly discarded. After use, put rags in water or lay rags out flat to dry before discarding.

#### 6.4. Reference to other sections

No data available.

## **SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

#### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

### Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

### 7.2. Conditions for safe storage, including any incompatibilities

Do not keep in plastic containers - may soften plastic.

Stock between +5°C and +30°C in a dry, well ventilated place.

#### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

## Packaging

Always keep in packaging made of an identical material to the original.

Recommended types of packaging :

- Vats
- Drums
- Buckets
- Suitable packaging materials :
- Metal
- Unsuitable packaging materials :
- Plastic

### 7.3. Specific end use(s)

No data available.

### SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

No data available.

### 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation,

## especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

Permeability time : >480 min for a thickness >0.45 mm

CEN recommendations : EN 420 and EN 374/3

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact. Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

### Respiratory protection

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP2

Type of mask with combined filters :

Wear a half mask in accordance with standard EN140.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

- AX (Brown)

Particle filter according to standard EN143 :

- P2 (White)

CEN recommendations : EN 136, EN 140, EN 405 for masks and EN 143, EN 149 for filters.

### SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

General information :	
Physical state :	Fluid liquid.
Colour :	Amber
Important health, safety and environmental information	
pH :	Not relevant.
Boiling point/boiling range :	Not relevant.
Flash Point :	63.00 °C.
Vapour pressure (50°C) :	Not relevant.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)	Version 25.1 (07-02-2019) - Page 5/8
RUSTOL-OWATROL / OWATROL OIL - RO001	
Vapour density :	>1
Density :	<1
Water solubility :	Insoluble.
Viscosity :	v>20.5mm²/s (40°C)
	Method for determining the viscosity :
	ISO 3104 (Petroleum products - Transparent and opaque liquids -
	Determination of kinematic viscosity and calculation of dynamic
	viscosity).
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not relevant.
Decomposition point/decomposition range :	Not relevant.
% VOC :	<50%
9.2. Other information	
VOC (g/l) :	460

### **SECTION 10 : STABILITY AND REACTIVITY**

#### 10.1. Reactivity

### No data available.

#### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

#### 10.4. Conditions to avoid

Avoid :

- accumulation of electrostatic charges.

- flames and hot surfaces

Always stock in its original packaging. Do not transfer in another package.

## 10.5. Incompatible materials

No data available.

## 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

## SECTION 11 : TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

## 11.1.1. Substances

## Acute toxicity :

LENE
LD50 > 5000 mg/kg
Species : Rat
OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)
LD50 > 2000 mg/kg
Species : Rabbit
OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)
LC50 = 4.688 mg/l
Species : Rat
OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)
Duration of exposure : 4 h

RUSTOL-OWATROL / OWATROL OIL - RO001		version 23.1 (07-02-2019) - Page 6/6
HYDROCARBONS, C10-C13, N-ALKANES.	ISOALKANES, CYCLICS, <2% AROMATICS	
Oral route :	LD50 > 5000 mg/kg	
	Species : Rat	
	OCDE Ligne directrice 401 (Toxicité aig	uë par voie orale)
Dermal route :	LD50 > 5000 mg/kg	
	Species : Rabbit	
	OCDE Ligne directrice 402 (Toxicité aig	uë par voie cutanée)
Inhalation route (n/a):	LC50 = 4.951 mg/l	
	Species : Rat	
	OCDE Ligne directrice 403 (Toxicité aig Duration of exposure : 4 h	ue par inhalation)
Germ cell mutagenicity :		
HYDROCARBONS, C10, AROMATICS, <19	6 NAPHTALENE	
	No mutagenic effect.	
HYDROCARBONS, C10-C13, N-ALKANES.	ISOALKANES, CYCLICS, <2% AROMATICS	
,,	No mutagenic effect.	
Carcinogenicity :		
HYDROCARBONS, C10, AROMATICS, <19	6 NAPHTALENE	
Carcinogenicity Test :	Negative.	
	No carcinogenic effect.	
	ISOALKANES, CYCLICS, <2% AROMATICS	
Carcinogenicity Test :	Negative.	
	No carcinogenic effect.	
Reproductive toxicant :		
HYDROCARBONS, C10, AROMATICS, <1%	6 NAPHTALENE	
No toxic effect for reproduction		
	OCDE Ligne directrice 414 (Étude de la prénatal)	toxicite pour le developpement
HYDROCARBONS C10-C13 NLAI KANES	ISOALKANES, CYCLICS, <2% AROMATICS	
No toxic effect for reproduction	TO ALMANEO, OT OLIOO, ~2/0 ANOWATION	
	OCDE Ligne directrice 414 (Étude de la	toxicité pour le développement
	prénatal)	
11.1.2. Mixture		
Monograph(s) from the IARC (International A	Agency for Research on Cancer) :	
	not classifiable as to its carcinogenicity to humans.	
ECTION 12 : ECOLOGICAL INFORMATIC		
Harmful to aquatic life with long lasting effects The product must not be allowed to run into d		
12.1. Toxicity		
Insufficient data.		
12.1.1. Substances		
HYDROCARBONS, C10, AROMATICS, <19	6 NAPHTALENE	
Fish toxicity :	Species : Perca fluviatilis	
Crustacean toxicity :	EC50 <= 10 mg/l	
crudiadan toxidity .	Species : Daphnia magna	
	Duration of exposure : 48 h	
	$E_{Cr50} = 11 mc''$	
Algae toxicity :	ECr50 = 11 mg/l Species : Pseudokirchnerella subcapital	ta
	Duration of exposure : 72 h	<i>ц</i> а
	· · · · · · · · · · · · · · · · · · ·	

Version 25.1 (07-02-2019) - Page 6/8

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKA Fish toxicity :	NES, CYCLICS, <2% AROMATICS LC50 = 1000 mg/l Species : Oncorhynchus mykiss Duration of exposure : 96 h
Crustacean toxicity :	EC50 = 1000 mg/l Species : Daphnia magna Duration of exposure : 48 h
Algae toxicity :	ECr50 = 1000 mg/l Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h
12.1.2. Mixtures	
No aquatic toxicity data available for the mixture.	
12.2. Persistence and degradability	
12.2.1. Substances	
HYDROCARBONS, C10, AROMATICS, <1% NAPHTA	LENE
Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
HYDROCARBONS, C10-C13, N-ALKANES, ISOALKA Biodegradability :	NES, CYCLICS, <2% AROMATICS Rapidly degradable.
12.3. Bioaccumulative potential	

No data available.

#### 12.4. Mobility in soil

Contains volatile products that will disperse in air. Contains a solid phase.

12.5. Results of PBT and vPvB assessment

No data available.

#### 12.6. Other adverse effects

No data available.

### **SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC. Dirty sheets can be burnt but should not be stocked nor thrown into a bin. They should be spread out and dried before. This product dries with air contact producing an exothermic reaction. Danger of auto-ignition if these precautions are not respected.

#### 13.1. Waste treatment methods

Do not pour into drains or waterways.

### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

#### Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

15 01 10 \* packaging containing residues of or contaminated by dangerous substances

08 01 11 \* waste paint and varnish containing organic solvents or other dangerous substances

### **SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

-

14.4. Packing group

- 14.5. Environmental hazards
- -
- 14.6. Special precautions for user

### **SECTION 15 : REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/669 (ATP 11)

## - Container information:

No data available.

#### - Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) :

The permitted European level of VOC in this ready-to-use product is limited to 460 g/l.

The permitted European level of VOC in the ready-to-use product (category IIAh) is 750 g/l maximum (2007/2010).

- Particular provisions :

No data available.

### 15.2. Chemical safety assessment

No data available.

### **SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

### Wording of the phrases mentioned in section 3 :

H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.