

SAFETY DATA SHEET

Quick Drying Radiator Paint

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: Quick Drying Radiator Paint

Product description	: Paint
Product type	: Liquid.
UFI	: WXWA-UJ1G-HNJ8-JEF9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Consumer use Industrial use Professional use		
	Uses advised against	Reason
None identified.		-

1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium Telephone no.: +32 (0) 13 460 200 Fax no.: +32 (0) 13 460 201

Tor Coatings Limited Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom Telephone no.: +44 (0) 191 4106611 Fax no.: +44 (0) 191 4920125 enquiries@tor-coatings.com

e-mail address of person : rpmeurohas@rustoleum.eu responsible for this SDS

1.4 Emergency telephone number	
National advisory body/P	oison Centre
<u>Supplier</u>	
Telephone number	: +353 19014670
Hours of operation	: 24 / 7

SECTION 2: Hazards identification

 2.1 Classification of the substance or mixture

 Product definition
 : Mixture

 Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements					
Signal word	: No signal w	rord.			
Hazard statements	: No known s	significant effects or critic	al hazards.		
Date of issue/Date of revision	: 9/07/2021	Date of previous issue	: 9/07/2021	Version : 2	1/16

SECTION 2: Hazards identification

Precautionary statements	
General	 P103 - Read carefully and follow all instructions. P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	 P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Safety data sheet available on request.
Supplemental label elements : Detergents - Regulation (EC) No 907/2006	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requiren	<u>nents</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Ireland

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥25 - ≤50	Carc. 2, H351 (inhalation)	[1] [2] [*]
1,2-benzisothiazol-3(2H)-one	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	≤0,1	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1)	[1]
Date of issue/Date of revision	: 9/07/2021 Date of previous issue	e : 9/07/2021	Version : 2	2/16

Quick Drying Radiator Paint

SECTION 3: Composition/information on ingredients

			Aquatic Chronic 2, H411	
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	REACH #: 01-2120764691-48 EC: 611-341-5 CAS: 55965-84-9 Index: 613-167-00-5	≤0,1	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) See Section 16 for the full text of the H statements declared above.	[1]

Sweden

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with diameter \leq 10 µm not bound within a matrix.

SCL (Specific Concentration Limits)	
1,2-benzisothiazol-3(2H)-one	H317 = 0.05 %
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	H317 = 0.0015 %
ATE (acute toxicity estimates) Not applicable.	Not applicable.

Nanoform	
Particle characteristics	Particle Size
Contains >0.1% - <1% silicon dioxide CAS# 7631-86-9 / EC# 231-545-4	1-100 nm

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

No specific data.
No specific data.
No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large
	quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire. In case of fire, use D chemicals, CO2, alcohol resistant foam or water spray.	RY
Unsuitable extinguishing media	water jet	
5.2 Special hazards arising fr	n the substance or mixture	
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.	
Hazardous combustion products	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incider there is a fire. No action shall be taken involving any personal risk or without suitable training.	nt if
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection f chemical incidents.	for
Additional information	No unusual hazard if involved in a fire.	
Date of issue/Date of revision	: 9/07/2021 Date of previous issue : 9/07/2021 Version : 2	4/16

Date of issue/Date of revision	: 9/07/2021	Date of previous issue	: 9/07/2021	Version : 2	4/16

Quick Drying Radiator Paint

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: 0°C (32°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
titanium dioxide	DNEL	Long term Inhalation	10 mg/m ³	Workers	Local
	DNEL	Long term Oral	700 mg/kg bw/day	General population [Consumers]	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
titanium dioxide	Fresh water	0,127 mg/l	-
	Marine	>1 mg/l	-
	Sewage Treatment	>100 mg/l	-
	Plant		
	Fresh water sediment	>1000 mg/kg	-
	Marine water sediment	>100 mg/kg	-
	Soil	100 mg/kg	-

8.2 Exposure controls

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measure	<u>s</u>

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Recommended: safety glasses with side-shields (EN 166)
Skin protection	

Quick Drying Radiator Paint

SECTION 8: Exposure controls/personal protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection :		Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. For prolonged or repeated handling, use the following type of gloves: nitrile rubber (EN 374) (breakthrough time) >8hours
		The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	•	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 140).
Environmental exposure controls	-	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	: Liquid.
Colour	: White.
Odour	: Not available.
Odour threshold	: Not available.
Melting point/freezing point	: 0°C
Initial boiling point and boiling range	: >100°C (>212°F) [Literature]
Flammability (solid, gas)	 Non-flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. Nonflammable, but will burn on prolonged exposure to flame or high temperature.
Upper/lower flammability or explosive limits	: Not available.
Flash point	: Not relevant due to nature of the product.
Date of issue/Date of revision	: 9/07/2021 Date of previous issue : 9/07/2021 Version : 2 7/16

SECTION 9: Physical and chemical properties

Auto-ignition temperature	1	Not relevant due to nature of the product.
Decomposition temperature	÷	Not available.
рН	÷	8 [OECD 122]
pH : Justification	1	Not available.
Viscosity	÷	Dynamic: 80 mPa·s
Solubility(ies)	1	Soluble in the following materials: cold water and hot water. Very slightly soluble in the following materials: methanol and acetone.
Solubility in water	:	Not available.
Partition coefficient: n-octanol/ water	:	Not applicable.
Vapour pressure	÷	2,3 kPa (17,25 mm Hg) [calculated.]
Evaporation rate	1	<1 (butyl acetate = 1)
Relative density	1	1,37 to 1,38 [calculated.]
Density	:	1,373219 g/cm³ [20°C (68°F)] [calculated.]
Vapour density	÷	>1 [Air = 1]
Explosive properties	:	Not applicable.
Oxidising properties	:	Not available.
Particle characteristics		
Median particle size	÷	Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	 Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO2 and smoke can be generated.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-benzisothiazol-3(2H)-	LC50 Inhalation Dusts and	Rat	0,11 mg/l	4 hours
one	mists			
	LC50 Inhalation Dusts and	Rat - Male,	0,5 mg/l	4 hours
	mists	Female		
	LD50 Oral	Rat - Male	490 mg/kg	-
reaction mass of: 5-chloro-	LC50 Inhalation Dusts and	Rat - Male,	0,171 mg/l	4 hours
2-methyl-4-isothiazolin-	mists	Female		
3-one [EC no. 247-500-7]				
and 2-methyl-2H-isothiazol-				
3-one [EC no. 220-239-6] (3:				

Quick Drying Radiator Paint

SECTION 1	11: Toxicological information				
1)	LD50 Dermal LD50 Oral	Rabbit Rat	92,4 mg/kg 64 mg/kg	-	

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	490 64	N/A 92,4	N/A N/A	0,5 N/A	N/A 0,171

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 Percent	-
,	Skin - Severe irritant Eyes - Severe irritant	Rabbit Rabbit	-	-	1 to 4 hours -

Conclusion/Summary

Skin
Eyes

: Based on available data, the classification criteria are not met.

: Based on available data, the classification criteria are not met.

Respiratory

: Based on available data, the classification criteria are not met.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	skin skin	Guinea pig Guinea pig	Sensitising Sensitising

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Skin

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Conclusion/Summary	: Based on available data, the classification criteria are not met.	
Reproductive toxicity		
Conclusion/Summary	: Based on available data, the classification criteria are not met.	
Teratogenicity		
Conclusion/Summary	: Based on available data, the classification criteria are not met.	
Specific target organ toxici	ity (single exposure)	

Date of issue/Date of revision : 9/07/202	1 Date of previous issue	: 9/07/2021	Version : 2	9/16
---	--------------------------	-------------	-------------	------

Quick Drying Radiator Paint

SECTION 11: Toxicological information Not available. Specific target organ toxicity (repeated exposure) Not available. **Aspiration hazard** Not available. Information on likely routes : Routes of entry anticipated: Oral, Inhalation. Routes of entry not anticipated: Dermal. of exposure Potential acute health effects Eye contact : Slightly hazardous by the following route of exposure: of eye contact (non-irritant) Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion • No known significant effects or critical hazards. However, in compliance with good industrial hygiene practice, exposure to any chemical should be kept to a minimum. Symptoms related to the physical, chemical and toxicological characteristics : No specific data. Eye contact Inhalation : No specific data. Skin contact : No specific data. Ingestion : No specific data. Delayed and immediate effects as well as chronic effects from short and long-term exposure Short term exposure **Potential immediate** : Not available. effects : Not available. **Potential delayed effects** Long term exposure Potential immediate : Not available. effects **Potential delayed effects** : Not available. Potential chronic health effects Not available. **Conclusion/Summary** : Based on available data, the classification criteria are not met. General : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. **Reproductive toxicity** : No known significant effects or critical hazards. **Endocrine disrupting** : Not available. properties Other information : Not available.

Quick Drying Radiator Paint

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
1,2-benzisothiazol-3(2H)-one	Acute EC50 0,067 mg/l	Algae - Pseudokirchneriella	72 hours
		subcapitata	
	Acute EC50 0,11 mg/l	Algae	72 hours
	Acute EC50 0,9893 mg/l Marine water	Crustaceans - Opossum Shrimp	96 hours
	Acute EC50 2,94 mg/l Fresh water	Daphnia spec.	48 hours
	Acute LC50 8 to 13 mg/l	Fish - Alburnus alburnus	96 hours
	Acute LC50 2,18 mg/l Fresh water	Fish	96 hours
	Acute LC50 1,6 to 2,8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 90 mg/l	Aquatic plants - Phaseolus vulgaris	20 days
	Chronic NOEC 1,2 mg/l	Daphnia spec.	21 days
	Chronic NOEC 0,21 mg/l	Fish	28 days
	Chronic NOEL 0,0403 mg/l	Algae	72 hours
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Acute EC50 0,037 mg/l Fresh water	Algae	48 hours
	Acute EC50 0,16 mg/l Fresh water	Daphnia spec.	48 hours
	Acute LC50 0,19 mg/l Fresh water	Fish	96 hours
	Acute NOEC 0,004 mg/I Marine water	Algae	48 hours
	Chronic NOEC 0,18 mg/l	Daphnia spec.	21 days
	Chronic NOEC 0,02 mg/l Fresh water	Fish	38 days

Conclusion/Summary

: Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	OECD 301D	>90 % - Readily - 1 days >60 % - Readily - 28 days	-	-
	-	<50 % - 10 days	-	-
Conclusion/Summary	: This product ha	as not been tested for biodegrad	ation. Based on ava	ailable data, the

	classification criteria are not met.		
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
(2-methoxymethylethoxy) propanol	-	>50%; <1 day(s)	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	-0.83 to 0.75		low low

SECTION 12: Ecological information

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Nonvolatile liquid.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting	: No known significant effects or critical hazards.
properties	
12.7 Other adverse effects	: No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	 Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
European waste catalog	ue (EWC)
Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

Quick Drying Radiator Paint

SECTION 14: Transport information

14.6 Special precautions for	1	Transport within user's premises: always transport in closed containers that are
user		upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
		···· ···· ··· ···· ···················

14.7 Transport in bulk	: Not available.
according to IMO	
instruments	

SECTION 15: Regulatory information

15.1 Safety, health and envir	onmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 190	<u>17/2006 (REACH)</u>
Annex XIV - List of substa	nces subject to authorisation
<u>Annex XIV</u>	
None of the components a	re listed.
Substances of very high	<u>concern</u>
None of the components a	re listed.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Other EU regulations	
VOC	: The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.
VOC for Ready-for-Use Mixture	: IIA/i. One-pack performance coatings. EU limit value for this product : 140g/l (2010.) This product contains a maximum of 70 g/l VOC.
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Ozone depleting substance Not listed.	<u>es (1005/2009/EC)</u>
Prior Informed Consent (P Not listed.	<u>PIC) (649/2012/EC)</u>
Persistent Organic Polluta Not listed.	ants (850/2004/EC)
<u>Seveso Directive</u> This product is not controlled <u>Ireland</u>	d under the Seveso Directive.

Quick Drying Radiator Paint

SECTION 15: Regulatory information References : Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001 (S.I. No. 619 of 2001) Safety, Health and Welfare at Work (Carcinogens) Regulations 2001 (S.I. No. 78 of 2001) Safety, Health and Welfare at Work (General Application) Regulations 2007 Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878 REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

International regulations

Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

List name		Ingredient name	Status
Not listed.			
CN code : 3209 90	00 00	ł	I
Inventory list			
Australia	: Not	determined.	
Canada	: Not	determined.	
China	: At le	ast one component is not listed.	
Europe	: All c	omponents are listed or exempted.	
Japan		Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.	
New Zealand	: Not	determined.	
Philippines	: Not	determined.	
Republic of Korea	: At le	At least one component is not listed.	
Taiwan	: All c	All components are listed or exempted.	
Thailand	: Not	Not determined.	
Turkey	: Not	Not determined.	
United States	: Not	determined.	
Viet Nam	: Not	determined.	
5.2 Chemical safety ssessment		product contains substances for which Chei ired.	mical Safety Assessments are sti

SECTION 16: Other information

Indicates information that h	as changed from previously issued versi	ion.	
Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and F 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Haza N/A = Not available PBT = Persistent, Bioaccumulative a PNEC = Predicted No Effect Concent	and Toxic	
Date of issue/Date of revision	: 9/07/2021 Date of previous issue	: 9/07/2021 Version : 2 14/	/16

Quick Drying Radiator Paint

SECTION 16: Other information RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Classification **Justification** Not classified. Full text of abbreviated H statements Ireland Full text of abbreviated H ż H301 Toxic if swallowed. statements 1202 Harmful if swallowed

statements	H302 Harmful if swallowed.
	H310 Fatal in contact with skin.
	H314 Causes severe skin burns and eye damage.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H318 Causes serious eye damage.
	H330 Fatal if inhaled.
	H400 Very toxic to aquatic life.
	H410 Very toxic to aquatic life with long lasting effects.
	H411 Toxic to aquatic life with long lasting effects.
Full text of classifications	Acute Tox. 2 ACUTE TOXICITY - Category 2
[CLP/GHS]	Acute Tox. 3 ACUTE TOXICITY - Category 3
	Acute Tox. 4 ACUTE TOXICITY - Category 4
	Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
	Aquatic LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
	Chronic 1
	Aquatic LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
	Chronic 2
	Carc. 2 CARCINOGENICITY - Category 2
	Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
	Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B
	Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1 SKIN SENSITISATION - Category 1
	Skin Sens. 1A SKIN SENSITISATION - Category 1A
Date of printing	9/07/2021
Date of issue/ Date of	9/07/2021
revision	
Date of previous issue	9/07/2021
Version	2
Notice to reader	

Notice to reader

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage,

Quick Drying Radiator Paint

SECTION 16: Other information

use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.