

# SAFETY DATA SHEET EASIPASTE WALLCOVERING ADHESIVE

# 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME EASIPASTE WALLCOVERING ADHESIVE

SUPPLIER Bartoline Limited

Barmston Close Beverley East Yorkshire HU17 0LW Tel. 01482 678710

Fax 01482 872606 HSE Manager

Email info@bartoline.co.uk

APPLICATION Adhesive for fixing wallcoverings

EMERGENCY TELEPHONE 01482 678727 0800-1700

## 2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

Prolonged contat with the skin may cause irritation

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
1,2-BENZISOTHIAZOL-3(2H)-ONE	220-120-9	2634-33-5	< 1%	Xn;R22 R43 Xi;R38,R41 N;R50
2-METHYLISOTHIAZOL-3(2H)-ONE	220-239-6	2682-20-4	0.0075%	T;R23. Xn;R22. C;R34. N;R50. R43.
2-OCTYL-2H-ISOTHIAZOL-3-ONE	247-761-7	26530-20-1	0.0075%	T;R23/24 C;R34 Xn;R22 R43 N;R50/53
CITRIC ACID			0.09%	Xi;R36.
GENERIC NON-HAZARDOUS - POWDER			1-5%	-

The Full Text for all R-Phrases are Displayed in Section 16

# **COMPOSITION COMMENTS**

This product is a non hazardous water based emulsion adhesive containing no hazardous ingredients in quantities greater than those laid down in Annex VI to directive 67/548 and The Dangerous Preparations Directive 1999/45/EC.

# 4 FIRST-AID MEASURES

# INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

# INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

#### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

# **EYE CONTACT**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## **5 FIRE-FIGHTING MEASURES**

# **EASIPASTE WALLCOVERING ADHESIVE**

#### **EXTINGUISHING MEDIA**

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

# SPECIAL FIRE FIGHTING PROCEDURES

Keep run-off water out of sewers and water sources. Dike for water control. If risk of water pollution occurs, notify appropriate authorities.

# **UNUSUAL FIRE & EXPLOSION HAZARDS**

No unusual fire or explosion hazards noted.

SPECIFIC HAZARDS

Not relevant.

PROTECTIVE MEASURES IN FIRE

Use protective equipment appropriate for surrounding materials.

## **6 ACCIDENTAL RELEASE MEASURES**

#### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

# **ENVIRONMENTAL PRECAUTIONS**

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

## SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

# 7 HANDLING AND STORAGE

#### **USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

## STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep in original container. Store above freezing.

STORAGE CLASS

Unspecified storage.

# 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
1,2-BENZISOTHIAZOL-3(2H)-ONE	WEL	2 ppm				

WEL = Workplace Exposure Limit.

#### PROTECTIVE EQUIPMENT





#### **ENGINEERING MEASURES**

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

# RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

## HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

# **EYE PROTECTION**

If risk of splashing, wear safety goggles or face shield.

# OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

# **EASIPASTE WALLCOVERING ADHESIVE**

## HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Liquid

COLOUR White / off-white

ODOUR Mild

SOLUBILITY Soluble in water.

RELATIVE DENSITY 0.98-1.08 pH-VALUE, CONC. SOLUTION 7.0-7.5
VISCOSITY 300-350 cSt 25 VOLATILE ORGANIC COMPOUND 126.75 g/l

(VOC)

# 10 STABILITY AND REACTIVITY

**STABILITY** 

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS POLYMERISATION

Will not polymerise.

MATERIALS TO AVOID

No incompatible groups noted.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

#### 11 TOXICOLOGICAL INFORMATION

# **GENERAL INFORMATION**

No specific health warnings noted. This product has low toxicity. Only large volumes may have adverse impact on human health.

**INHALATION** 

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Prolonged contact may cause dryness of the skin.

**EYE CONTACT** 

May cause temporary eye irritation.

ROUTE OF ENTRY

Skin and/or eye contact.

**TARGET ORGANS** 

Eyes. Skin.

MEDICAL SYMPTOMS

Irritation of eyes and mucous membranes. Dry skin.

# 12 ECOLOGICAL INFORMATION

# **ECOTOXICITY**

Not regarded as dangerous for the environment.

**MOBILITY** 

The product is non-volatile. The product is miscible with water. May spread in water systems.

BIOACCUMULATION

No data available on bioaccumulation.

# **EASIPASTE WALLCOVERING ADHESIVE**

# ACUTE FISH TOXICITY

The addition of large ammounts into watercourses may cause the pH to rise and may therefore be harmful to aquatic life in some circumstances

# 13 DISPOSAL CONSIDERATIONS

**DISPOSAL METHODS** 

Dispose of waste and residues in accordance with local authority requirements.

WASTE CLASS

When this product, in its liquid state, as supplied, becomes waste, it is categorised as non-hazardous, with code 08 04 10. Part used containers, not drained and/rigourously scraped out and containing dried residues of the supplied coating are categorised as non-hazardous waste with code 08 04 10. Used containers, drained and or rigoursouly scraped out and containing dried residues of the supplied coating are categorised as non-hazardous waste with code 15 01 02.

## 14 TRANSPORT INFORMATION

GENERAL The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA,

ADR/RID).

No transport warning sign required.

ROAD TRANSPORT NOTES

RAIL TRANSPORT NOTES

SEA TRANSPORT NOTES

AIR TRANSPORT NOTES

Not classified.

Not classified.

# 15 REGULATORY INFORMATION

**RISK PHRASES** 

NC Not classified.

SAFETY PHRASES

NC Not classified.

**EU DIRECTIVES** 

Dangerous Preparations Directive 1999/45/EC.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

**GUIDANCE NOTES** 

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

# **16 OTHER INFORMATION**

REVISION DATE 20/05/2010

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R34 Causes burns.

R22 Harmful if swallowed.

R36 Irritating to eyes.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R41 Risk of serious damage to eyes.

R23/24 Toxic by inhalation and in contact with skin.

R23 Toxic by inhalation.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R50 Very toxic to aquatic organisms.

**REVISION DATE: 20/05/2010** 

# **EASIPASTE WALLCOVERING ADHESIVE**

## **DISCLAIMER**

The information contained in this data sheet is provided in accordance with the requirements of the Chemicals (Hazard Information and Packaging for Supply) Regulations. The product should not be used for purposes other than those shown in Section 1. As the specific conditions of use are outside the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet is based on the present knowledge and the current UK legislation and EC Directive 91/155EC. It provides guidance on health, safety and environmental aspects of the product and should not be taken as a product specification.